

Elettronica Santerno S.p.A.
Strada Statale Selice, 47
40026 Imola (Bo) Italia
t +39 0542 489711
f +39 0542 489722
info@santerno.com
santerno.com



Stabilimento Produttivo
Via della Concia, 7
40023 Castel Guelfo
(BO) Italia
t +39 0542 489311

SUNWAY TG STANDARD series

SUNWAY TG760 1000V TE - 360 STD

Indoor Application

Uffici Milano
Via Giotto, 4
20040 Cambiagio
(Mi) Italia
t +39 02 95138126
t +39 02 95179254
t +39 02 95179458
f +39 02 95139216

Sede Legale
Via Olmo, 37
35011 Campodarsego
(Pd) Italia
t +39 049 9219111
f +39 049 9289111

Cap. Soc. € 2.500.000 i.v.
Codice Fiscale e Partita Iva
03686440284
R.E.A. PD 328951
Cod. Mecc. PD 054138
Cod. Ident. IVA Intracom.
IT03686440284

Elettronica Santerno S.p.A.
Società soggetta all'attività
di direzione e coordinamento
di Carraro S.p.A.



Designed for utility scale applications, **SUNWAY TG** inverters feature best-in-class technology without compromises providing the highest power density and reliability.

Thanks to the intrinsic flexibility, **SUNWAY TG** product range allows the optimal configuration of medium and large PV plants providing the lowest system cost and the maximum yield.

SUNWAY TG inverters are designed and manufactured in Italy by technicians and engineers of Elettronica Santerno S.p.A.

BENEFITS

- Very high conversion efficiency with a single power conversion stage, optimized for minimum losses
- Modular construction and cabinet industrialization for maximum reliability and easy access to all components for maintainability and ease of service on site
- Grid Code integrated features (LVRT, Reactive Power Control, Frequency and Voltage control) in compliance with the most advanced European and WW standards
- Remote monitoring possibility with SunwayPortal and REMOTE SUNWAY™ software both for a single device and a multi-inverter installation
- Integrated DC-side protection provided by disconnect switch with release coil
- Integrated miswiring protection on DC side
- Integrated AC-side protection with automatic-disconnection on load breaker
- Integrated active monitoring of DC isolation
- Integrated Modbus on RS485 and TCP-IP on Ethernet data connection
- Integrated inputs for environmental sensors
- Possibility to install photovoltaic modules requiring one earthed pole, both positive and negative pole
- Thorough manufacture with first class materials, fully Made in Italy

| Main features | |
|---|---------------------------------|
| Model | SUNWAY TG760 1000V TE - 360 STD |
| MPPT voltage range ⁽¹⁾ | 550 - 820 V |
| Number of independent MPPT | 1 |
| Max. Open-circuit voltage | 1000 V |
| Rated AC voltage | 360 V ± 10 % |
| Rated output frequency | 50 / 60 Hz (up to -3 / +2 Hz) |
| Power Factor @ rated power | 1 - 0.9 lead/lag |
| Operating temperature range | -25 ÷ 62 °C |
| Application / Degree of protection | Indoor / IP20 |
| Maximum operating altitude ⁽²⁾ | 4000 m |

| Input Ratings (DC) | |
|---|-----------------------------|
| Rated input power | 824 kW |
| Maximum short circuit PV input current | 1500 A |
| PV Voltage Ripple | <1% |
| Output Ratings (AC) | |
| Rated output power @ 50°C | 800 kVA |
| Rated output current | 1283 A |
| Power threshold | 1% of Rated AC output power |
| Total AC current distortion | ≤ 3% |
| Inverter efficiency | |
| Maximum / EU/ CEC efficiency ⁽³⁾ | 98.6 % / 98.3 % / 98.0 % |
| Dimensions and weight | |
| Inverter Dimensions (WxHxD) | 2600 x 2250 x 800 mm |
| Inverter Weight | 2000 kg |
| Auxiliary Consumptions | |
| Stop mode losses/Night losses | 45 W / 45 W |
| Auxiliary consumption | 2165 W |
| Optional Anticondensation heater consumption ⁽⁴⁾ | 1 kW |

Elettronica Santerno reserves the right to make any technical changes to this document without prior notice.

NOTE

⁽¹⁾ At Vac rated and Cos φ =1

⁽²⁾ Up to 1000 m without derating

⁽³⁾ Auxiliary consumptions are not considered when measuring the conversion efficiency

⁽⁴⁾ Optional recommended for Outdoor application in cold climate environments

| Additional information | |
|---|--|
| Protection against overvoltage (SPD) | DC Side: Yes - AC Side: Optional |
| Maximum value for relative humidity | 95% no condensing |
| Cooling system / Fresh air consumption | Forced air / 12000 m ³ /h |
| Thermal protection | Integrated, 5 sensors, both on cabinet and power stack |
| Environmental sensors | 4 embedded inputs |
| Digital communications channels | 2xRS485 with Modbus + Ethernet with TCP/IP |
| Noise emission @ 1m / 10m ⁽⁵⁾ | 78 / 58 dB |
| Connection phases | 3 |
| Max DC inputs per pole/ fuse protected ⁽⁶⁾ | 8 + 8 / 0 |
| DC Parallel included | No |
| DC inputs current monitoring | Optional |
| DC side disconnection device | DC disconnect switch |
| AC side disconnection device | AC circuit breaker |
| Ground fault monitoring, DC side | Yes |
| Ground fault monitoring, AC side | Optional |
| Grid fault monitoring | Yes |
| Display | Alphanumeric display/keypad |
| Power modulation | Via Remote Control (RS485, Ethernet) and analog |
| RAL | RAL 7035 |
| PV plant monitoring | Optional (Via Sunway Portal) |

Elettronica Santerno reserves the right to make any technical changes to this document without prior notice.

NOTE

⁽⁵⁾ Noise level measured in central and front position

⁽⁶⁾ Fuses to be ordered separately

Description of Operation

SUNWAY TG are grid connected solar inverters, suitable for connection to LV or MV distribution lines, as well as HV transport grids.

Advanced grid interface, certified in compliance with the most advanced requirements, ensures reliability and maximum uptime, providing grid support features such as FRT, active power modulation, voltage control. Utility Interactive Features are embedded, software-controlled, completely configurable based on the applicable grid code.

Moreover, Sunway TG inverters can be integrated in smart grid plants, installed together with off-grid inverters.

Best reliability is ensured by design. All electronics PCBs are coated for best protection against harsh environment. Redundant protection systems and auto-diagnostic functions are also implemented.

Auxiliary power and LVRT are self-supplied. Neither external power nor UPS is needed; however, an external source may be connected, if desired.


PV earthing

Optionally, the **SUNWAY TG** inverters can be provided with positive- or negative- ground connection of the PV field. That configuration shall be defined when ordering the equipment and it is recommended in case of modules sensitive to the PID (potentially induced degradation) are adopted.

Standard Supply

All inverters are supplied with user manuals, technical documents complying with the regulations in force, keys and lifting hooks, special pallets for easy and safe transport.

Layout



Main Normative References

The **SUNWAY TG** inverters have been developed, designed and manufactured in accordance with the up-to-date requirements of the Low Voltage directives, Electromagnetic Compatibility directives and Grid Connection standards

| Standards ⁽⁷⁾ | |
|--------------------------|--|
| Certification | CE, BDEW , CQC ,CSA |
| Immunity | IEC 61000-6-4, IEC 61000-6-2 |
| Harmonics | IEC 61000-3-2, IEC 61000-3-12 |
| Emissions | IEC 61000-6-3, IEC 61000-6-1 |
| Safety | EN50178, IEC 62109-1, IEC 62109-2 |
| Grid connection | CEI 0-16, A.70, BDEW, Arrêté du 23 Avril 2008, RD 1699/2011, RD 661/2007, CQC, IEEE 1547 |

NOTE

⁽⁷⁾ Some standard available only on specific models